



DESIGN STANDARD/设计标准	EN1171	
FACE TO FACE/结构长度	DIN3202 F4	
END FLANGE /连接法兰	BS4504/BS EN 1092	
TEST/检验	EN1074	
HYDRAULIC INSPECTION/压力试验		
TEST PRESSURE / 试验压力 Mpa	DODY / 强度	2.4
	SEAT / 密封	1.76
适用于淡水、空气或其他气体、油，温度不高于70℃		

DN600	390	600	840	720	770	20-φ37	720	1320	36	5
DN500	350	500	715	609	650	20-φ34	582	1140	31.5	4
DN450	330	450	640	548	585	20-φ31	640	1020	30	4
DN400	310	400	580	480	525	16-φ31	640	930	28	4
DN350	290	350	520	429	470	16-φ28	640	810	36.5	4
DN300	270	300	460	370	410	12-φ28	500	716	24.5	4
DN250	250	250	405	319	355	12-φ28	800	628	22	3
DN200	230	200	340	266	295	12-φ23	360	520	20	3
DN150	210	150	285	211	240	8-φ23	360	422	19	3
DN100	190	100	220	156	180	8-φ19	280	325	19	3
DN80	180	80	200	132	160	8-φ19	280	290	19	3
DN65	170	65	185	118	145	4-φ19	280	255	19	3
DN50	150	50	165	99	125	4-φ19	280	239	19	3
DN	L	d	D	D1	C	N-V	P	H	b	t

11	手轮	QT500	Hand wheel	Ductile Iron
10	防尘圈	EPDM	Wiper ring	EPDM
9	O形圈	EPDM	O-rings	EPDM
8	压盖	QT500	Gland	Ductile Iron
7	垫片	ZQSn5-5-5	washers	Gun metal
6	阀盖	QT500	Bonnet	Ductile Iron
5	密封圈	EPDM	Bonnet gasket	EPDM
4	阀杆	2Cr13	Spindle	Stainless Steel 420S37
3	阀杆螺母	ZQSn5-5-5	Gate nut	Brass
2	闸板	QT500 + 青铜	Wedge	Ductile Iron + BRONE
1	阀体	QT500	Body	Ductile Iron
序号	名称	材料	NAME OF PART	MATERIAL

法兰球铁硬密封闸阀(PN16) GATE VALVE (METAL SEATS) PN16



江苏竹美阀业有限公司

JIANGSU ZUZEM VALVES CO., LTD